

MAIN PROCESS & SPECIFICATIONS	PROCESSING METHODS	PROCESS CAPABILITY	CAAS, FAA & EASA CERTIFIED	NADCAP ACCREDITED	ON SITE
<p>Fluorescent Penetrant Inspection (FPI)</p> <p>ASTM E1417, SPOP 62, SPOP 82, HS 447, PN 16.03, FEIS 701B, 981-060-021</p>	<p>Penetrant Type: Type I – Fluorescent Penetrant (In accordance with QPL-AMS 2644)</p> <p>Penetrant Removal Methods: Method A Water Washable</p> <p>Method C Solvent Removable</p> <p>Method D Hydrophilic Post-Emulsified</p> <p>Penetrant Sensitivity and Method by Spray Application: Level 2 – Method A & D Level 3 – Method A & D Level 4 – Method D</p> <p>Developer: Form a – Dry Powder (Dust Storm Application) Form d – Non-aqueous Wet Developer (Solvent Based)</p>	<p>Oven, Emulsifier and Developer Tank Dimensions:</p> <p>(1) Depth: 800 mm, Length: 1600 mm, Width: 680 mm</p> <p>(2) Depth: 1000 mm, Length: 1240 mm, Width: 1000 mm</p> <p>Hoist for heavy parts up to 500kg</p>	✓	✓	✓
<p>Magnetic Particle Inspection (MPI)</p> <p>ASTM E1444, SPOP 102, SPOP 105, HS 31, PN 16.04, FEIS 701A, 981-060-014</p>	<p>Magnetization Methods: - Direct contact, - Indirect magnetization, - Induced current magnetization (Toroidal)</p>	<p>MPI machines (Magnaflux) 3 Phase Full Wave DC, 25 inch coil, 6000 Amp</p> <p>Processing Capability: Max part length: 1340 mm Max part diameter: 630 mm</p> <p>Yoke (AC & DC) Fluorescent Magnetic Ink</p>	✓	✓	✓
<p>Eddy Current Testing (ET)</p> <p>ASTM E376, ASTM E1004</p>	<p>High Frequency Eddy Current Testing, Low Frequency Eddy Current Testing, Conductivity Testing, Flaw Detection</p>	<p>Nortec 500S</p>	✓		✓
<p>Ultrasonic Testing (UT)</p> <p>ASTM E114, ASTM E797/797M</p>	<p>Contact Testing, Thickness Gauging, Flaw Detection</p>	<p>Epoch 600</p>	✓		✓